

The logo for STURDY LADDER INC. features the word "STURDY" in a large, bold, black sans-serif font. Above and below the word are two thick, horizontal red bars. The letters are white against the black background of the bars.

L A D D E R I N C .

4209 – 17A STREET SE
CALGARY, AB, T2G 3X1
TEL: (403) 264-2934
FAX: (403) 264-2998
e-mail: info@sturdyladder.com

Model 130 / 140 Operating Instructions

TRADE-NAMES: SAWHORSE, WORK-STAND,
WALK-UP SCAFFOLD, SAWHORSE BENCH.

PLEASE READ CAREFULLY: This product may be used in several different ways:

- 1) Step Stool;
- 2) Trestle Ladder;
- 3) Ladder-Type Scaffold;

Inspection:

- 1) Inspect product upon receipt and before each use.
- 2) Make sure all rivets and joints, nuts and bolts are tight and secure.
- 3) Never use a damaged, bent or broken product.
- 4) Never make temporary repairs of damaged or missing parts.
- 5) All parts must be in good working order.

Selection:

- 1) Select product of proper length to reach working height. Maximum height available for Model 130 is 10' and for Model 140 is 4'.
- 2) Model 130 and Model 140 have passed all the required tests of ANSI 14.2 - Type 1A (300 Lbs duty rating) for trestle ladders and step stools.
- 3) Model 130 and Model 140 have sustained a maximum load of over 2,400 lbs on the top cap and are duty rated for 500 Lbs when used in a Ladder - Type scaffold or scaffold platform situation.
- 4) The combined weight of workers, planks, platforms, support equipment and any materials on the platforms shall not exceed the sum of the rated capacity on the product.

CAUTION:

- 1) DANGER! This product is made of metal and can conduct electricity.
- 2) Do not let product come in contact with live electrical wires.
- 3) Do not use this product if you tire easily, are subject to fainting spells, are using medicine or alcohol, or are physically handicapped.

Setup:

- 1) Always set up product on a firm level surface and ensure a secure footing. Do not place product on slippery surfaces.
- 2) When setting up this product ensure that the spreaders are in the locked position.
- 3) Do not setup in front of doors that can open towards the product.
- 4) To protect children, do not leave product setup and unattended.

Proper Use:

- 1) Step Stool:
 - Model 130 and Model 140 at 2' and 2-1/2' conform ANSI 14.2 and may be used as a step stool (Section 6.6.1).
 - When used as a step stool standing on the top is permitted per ANSI 14.2 Section 3.
- 2) Trestle Ladder:
 - Model 130 and Model 140 at 3' and higher conform with ANSI 14.2 and may be used as a trestle ladder.
 - When used as a Trestle ladder, one may not stand on the top cap or the first step down.
 - When used as a Trestle ladder, this product permits the use by two people at once, one on each side.
- 3) Ladder-Type Scaffold:
 - This product has been designed and tested to be used as a Ladder-Type scaffold as per ANSI 10.8 Section 17 when used in conjunction with an appropriately designed plank.
 - This product has been designed to support a plank and provide access and egress to the plank.
 - Straddle two benches with a plank that is a minimum of 12" wide. The plank must overlap the supporting steps by at least 12", but not more than 18" at each end.
 - The maximum height of the working surface for Ladder-Type scaffolds shall not be more than four times the outside base width of the bench unless tied-off.
 - Planks and platforms shall be securely fastened to the supporting members to prevent lateral movement and shall overhang the supporting member by a minimum of 12 inches and a maximum of 18".